



10/100/1000 Bypass Switch with Heartbeat™

Net Optics 10/100/1000 Bypass Switches with Heartbeat™ provide permanent and trouble-free access ports for in-line network security and monitoring devices. The Bypass Switch automatically switches network traffic through added in-line devices or bypasses devices that are about to be removed. With a heartbeat, the 10/100/1000 Bypass Switch protects network traffic against link, application, and power loss on the attached in-line device.

The 10/100/1000 Bypass Switch with Heartbeat monitors the link to the attached in-line device by sending a heartbeat packet to the device once every second. If the Bypass Switch does not receive the heartbeat back, Fast Path™ switching automatically diverts network traffic to bypass the unresponsive device — even if the device is still receiving power. The Bypass Switch continues to send the heartbeat and restores the traffic through the in-line device as soon as the link is restored.

Each 10/100/1000 Bypass Switch includes all the cables and power supplies necessary to connect to an IPS. For special applications, the bypass trigger, heartbeat rate, and heartbeat packet can be customized from an RS232 command line interface.

Passive, Secure Technology

- Fail-safe monitoring with any 10/100/1000 GigaBit in-line appliance
- Increased reliability on critical network links
- High-speed Fast Path™ switching with minimal traffic interruption
- Link Fault Detect prevents undetected link failures
- Customizable behavior via command line interface

Ease of Use

- LED indicators show power, speed, link, and activity status
- Front-mounted connectors support easy installation and operation
- Cables included for plug-and-play deployment
- Silk-screened application diagram illustrates all connections for easy deployment
- Optional 19-inch rack frames holds two Bypass Switches
- Compatible with all major manufacturers' monitoring devices, including protocol analyzers, probes, and intrusion detection/prevention systems



Operating Specifications:

Operating:

Operating Temperature: 0°C to 55°C

Storage Temperature: -10°C to 70°C

Relative Humidity: 10% min, 95% max, non-condensing

Mechanical:

Power Supply:

Input: 100-240V, 0.5A, 47-63Hz

Output: 12V 3A

Dimensions: 1.125" high x 10" deep x 6.5" wide

Cable Interface:

Copper Cable Type:

22-24 AWG unshielded twisted pair cable, CAT5/CAT5E

Link Distance Supported: 100 meters

Connectors:

Monitoring Ports: (2) RJ45, 8 pin connectors

Network Ports: (2) RJ45, 8 pin connectors

Certifications:

Fully RoHS compliant

Part Number	Description
BP-HBCU3	10/100/1000 Bypass Switch w/Heartbeat
RK-2V2	Two-Slot Rackmount Frame

All products include a 1 year manufacturer's warranty. An additional 1 or 2 year extended warranty may also be purchased.

Distributed by:

BRAIN FORCE
smart IT for your business

BRAIN FORCE Software GmbH
Ohmstr. 12
63225 Langen
Germany

T: +49 6103 906 767
netoptics@brainforce.com
www.network-taps.eu

Net Optics Inc., 5303 Betsy Ross Drive, Santa Clara, CA 95054, USA
Tel: +1 (408) 737-7777 • www.netoptics.com

Net Optics® is a registered trademark of Net Optics, Inc. Copyright 1996-2007 Net Optics, Inc. All rights reserved. Additional company and product names may be trademarks or registered trademarks of the individual companies and are respectfully acknowledged. PUBBPHBCU3D Rev. 2, 03/07