

10 GigaBit Media Converter

Net Optics 10 GigaBit Converters are optimized, high-performance media converters for connecting dissimilar 10 GigaBit devices and links. Deploy these bidirectional media converters individually to connect SR or LR fiber devices, or in pairs at each end of long-distance fiber links. These Converters are the perfect solution for dispersed networks where media conversion is required between multimode segments separated by long distances.

The 10 GigaBit Converters support seamless media conversion at 10 Gbps over link distances up to 65 meters with SR fiber or 10 kilometers with LR fiber. To control jitter over long optical links, the Converter features Clock and Data Recovery (CDR). These Converters feature XFP module connectors for quick reconfiguration and redeployment.

All network and monitoring cables necessary for plug-and-play deployment are included with the Tap. For extra uptime protection, Net Optics Converters offer redundant power connections. Should the primary power source fail, the Converter automatically switches to the backup power source.

Secure Technology

- Optimized and tested for 10 GigaBit fiber networks
- Provides transparent conversion at 10 Gbps without data stream interference or introducing a point of failure
- Clock and Data Recovery (CDR) control overall jitter when deploying converter pairs
- Redundant power ensures monitoring uptime
- Compatible with all 10 GigaBit LR singlemode fibers and SR multimode fiber

Ease of Use

- LED indicators show link status and redundant power
- XFP connectors support easy reconfiguration and redeployment
- Optional 19-inch rack frame holds three Converters
- Optional Conversion kits include transceiver and cable
- Tested and compatible with all major manufacturers' monitoring devices, including protocol analyzers, probes, and intrusion detection/prevention systems



Technical Specifications:

Operating Specifications:

Operating Temperature: 0°C to 40°C
 Storage Temperature: -10°C to 70°C
 Relative Humidity: 5% min, 95% max, non-condensing

Mechanical Specifications:

Power Supply:
 Input: 100-240 VAC, 50-60 Hz, 0.6A, Output: 12VDC, 1.5A
 Dimensions: 1.25" high x 5.25" deep x 4.5" wide

Optical Specifications:

10GBase-SR XFP:
 Fiber Type: Corning Multimode 50µm or 62.5µm, wavelength 850nm
 Input Sensitivity: -11.1 dBm
 Output Power: -7.3 dBm min to -1 dBm max

10GBase-LR XFP:
 Fiber Type: Corning Singlemode 8.5µm, wavelength 1310nm
 Input Sensitivity: -12.6 dBm
 Output Power: -0.5 dBm max

Connectors:

XFP: 10GBase-SR, -LR

Certifications:

Fully RoHS compliant
 Fully IEEE 802.3ae compliant

Part Number	Description
FMC-XFP	10 GigaBit Converter with XFPs
XFPKT-50SR	SR XFP Conversion Kit 50µm
XFPKT-SR	SR XFP Conversion Kit
XFPKT-LR	LR XFP Conversion Kit
RK-3V2	Three-slot panel for rack mounting
RK-12V2	Twelve-slot panel for rack mounting

All products include a 1 year manufacturer's warranty. An additional 1 or 2 year extended warranty may also be purchased. XFP kits are ordered separately (minimum order Qty. 2 per unit).

Net Optics® is a registered trademark of Net Optics, Inc. Copyright 1996-2010 Net Optics, Inc. All rights reserved. Additional company and product names may be trademarks or registered trademarks of the individual companies and are respectfully acknowledged. PUBFMCLRSRD Rev. 2, 03/07

Net Optics Inc., 5303 Betsy Ross Drive • Santa Clara, CA 95054
 Tel: +1 (408) 737-7777 • www.netoptics.com

Distributed by:

BRAIN FORCE
 smart IT for your business

BRAIN FORCE Software
 Ohmstr. 12
 63225 Langen
 Germany

T: +49 6103 906 767
 netoptics@brainforce.com
 www.network-taps.eu